VESSEL:		VIN:	DATE:	
INSPECTOR:		INSPECTION TYPE:	ACTIVITY #:	
	SPECTION REQUIREMENT OMOSASSA RIVER, FLORID		INGS BAY), RAINBOW RIVER AND Updated: 24DEC02	
1. 2.	Last dry dock date: State Registration current and Starboard Bows. (33CFR a. Vessel HIN:	173.27)	k: ion Certificate with 3" State Numbers on the Port	
3.	Passenger capacity. If Manufacturer Plate present-Passenger capacity will be computed by deck area, seating, or rail criteria (46CFR176.113) but can not be more than allowed by the manufacturers plate.			
	a. Manufacturer Plate Information: Total passengers: Total weight: Outboard engine HP: Weight: If Manufacturer Plate not present, stability letter date: On board: Y/N			
	Passenger capacity will be computed by deck area, seating, or rail criteria (46CFR176.113) but can not be than allowed by stability test & letter (46CFR178.340).			
4.	Crew is One (1) Coast Guard Licensed Master of Inland Waters for the area(s) Certificated & participating in an approved 46 CFR Part 16 Random Chemical Drug Testing Program.			
5.	Life Preservers – Type I adult life preserver required for all passengers and crew, add 10% child size PFD's for total persons.			
6.	Ring Buoy – If less than 26'-20" minimum ring buoy with a 60' line (3/8" minimum) attached. If 26' or more- 24" minimum ring buoy with a 60' line (3/8" minimum) attached.			
7. 8.	Lifesaving equipment markings – Ring buoy and life preservers marked with vessel's name or FL numbers. Flares –Night operations-3 red hand flares in a watertight box.(46CFR180.68). Day use only- 3 orange smokes in a watertight box or 1 orange flag.(33CFR175.130).			
9.	Suitable anchor with 50' of l	ine.		
10.	Navigation Lights – Meeting Inland Navigation Rules per ABYC A-16 Standards or UL approved lights. Otherwise restricted to daylight operations and restricted from conditions of restricted visibility.			
11.	Portable Fire Extinguisher – One B-I for boats under 26'. One B-II or two B-Is for 26' and over. (33CFR25.30-20).			
12.	2. Fuel Tank – ABYC or 33 Code of Federal Regulations approved fuel systems (includes hoses).			
13.	Bilge Pump – One hand portable bilge pump if vessel has open voids. NOT REQUIRED for sealed pontoon style boats, which must have fittings to allow installation of shrader valves.			
14.	Safety Railings – minimum 36" high except in way of the diver access where safety chains are permitted.			
15.	Possible dive ladder, dependi	ng on freeboard.		

ROUTES: A Certificate of Inspection issued for a vessel inspected using the above minimums is valid only for diving operations on the following waters and <u>MAY NOT</u> be transferred to any other route in this or any other inspection zone. Routes: Kings Bay, Crystal River, Rainbow River from headwater down stream approximately 2 miles to K.P. Hole and Homosassa River from headwater down stream to Channel marker 20, for Diving Operations only.

16. **Floating waterlight** – CG Approved 46 CFR 161.010 attached to ring buoy if operating at night.

18. **Sound Producing Device** (72 COLREGS)

17. VHF Radio – vessel restricted to 1,000' from shore with no radio, FCC station license and operator permit.